

BL192 Series



General Specifications

Partnumber	Voltage V	Length mm	Nominal torque mNm	Nominal speed rpm	Current at max torque A	Rotor
BL192-24-3	24	67,5	150	880	1,15	-
BL192-24-5	24	67,5	200	660	1,15	-
BL192-24-13	24	74,5	450	255	1,1	-
BL192-24-18	24	74,5	600	190	1,1	-
BL192-24-25	24	74,5	900	138	1,1	-
BL192-24-49	24	81,5	1600	68	1,1	-
BL192-24-67	24	81,5	2200	50	1,1	-
BL192-24-91	24	81,5	2700	37	1,15	-
BL192-24-125	24	81,5	3000	30	0,95	-
BL192-24-180	24	88,5	2200	24	0,63	-
BL192-24-246	24	88,5	3000	17	0,67	-
BL192-24-336	24	88,5	3000	13	0,56	-
BL192-24-458	24	88,5	3000	10	0,53	-
BL192-24-625	24	88,5	3000	7,5	0,43	-

Stegia AB

Regattagatan 22B
723 48 Västerås, Sweden
+46 (0) 21 811 822
info@stegia.com

Stegia Shanghai Co., Ltd.

A-7, No.38, Dongsheng Rd
Pudong, Shanghai, China, 201201
+86 21 58591682

Mechanical Dimensions

