

E192 Series



General Specifications

Partnumber	Voltage (V)	Reduction (:1)	Length (mm)	Diameter (mm)	Nominal torque (mNm)	Speed at nominal torque	Current (A)
E192-12-3	12	3,66	86	40,5	150	700	1,70
E192-24-3	24	3,66	86	40,5	150	770	0,96
E192-12-5	12	5	86	40,5	200	510	1,75
E192-24-5	24	5	86	40,5	200	575	0,95
E192-12-13	12	13,44	93	40,5	450	200	1,65
E192-24-13	24	13,44	93	40,5	450	225	0,85
E192-12-18	12	18,33	93	40,5	600	155	1,65
E192-24-18	24	18,33	93	40,5	600	170	0,84
E192-12-25	12	25	93	40,5	900	105	1,75
E192-24-25	24	25	93	40,5	900	118	0,88
E192-12-49	12	49,29	100	40,5	1600	60	1,60
E192-24-49	24	49,29	100	40,5	1600	67	0,85
E192-12-67	12	67,22	100	40,5	2200	40	1,80
E192-24-67	24	67,22	100	40,5	2200	45	0,88
E192-12-91	12	91,66	100	40,5	2700	31	1,70
E192-24-91	24	91,66	100	40,5	2700	34	0,85

Partnumber	Voltage (V)	Reduction (:1)	Length (mm)	Diameter (mm)	Nominal torque (mNm)	Speed at nominal torque	Current (A)
E192-12-125	12	125	100	40,5	3000	24	1,32
E192-24-125	24	125	100	40,5	3000	26	0,64
E192-12-180	12	180,75	107	40,5	3000	20	0,75
E192-24-180	24	180,75	107	40,5	3000	20	0,42
E192-12-246	12	246,48	107	40,5	3000	14,5	0,87
E192-24-246	24	246,48	107	40,5	3000	15	0,43
E192-12-336	12	336,11	107	40,5	3000	11	0,69
E192-24-336	24	336,11	107	40,5	3000	11,5	0,34
E192-12-458	12	458,33	107	40,5	3000	8,5	0,54
E192-24-458	24	458,33	107	40,5	3000	9	0,28
E192-12-625	12	625	107	40,5	3000	6	0,46
E192-24-625	24	625	107	40,5	3000	6,2	0,23

The resistance can be chosen with respect to the required torque and supplied voltage

- Planetary gear-motor
- Motor interference suppression by VDR and capacitors
- Outgoing shaft two ball bearings supported
- Maximum radial shaft load: 200N (10mm from the fixing flange)
- Maximum axial shaft load: 100N
- Direction of rotation depending on polarity
- Can be mounted in any position
- Working temperature range: -20°C/60°C
- Approx weight: 385/480g

