

RH158 Series



General Specifications

Partnumber	Voltage (V)	Reduction (:1)	Length (mm)	Diameter (mm)	Nominal torque (mNm)	Speed at nominal torque	Current (A)
RH158-12-15	12	14,14	64	40	100	300	0,66
RH158-24-15	24	14,14	64	40	100	300	0,33
RH158-12-30	12	29,75	64	40	200	140	0,66
RH158-24-30	24	29,75	64	40	200	140	0,33
RH158-12-75	12	76,84	66,5	40	500	55	0,68
RH158-24-75	24	76,84	66,5	40	500	55	0,34
RH158-12-100	12	94,37	66,5	40	600	45	0,68
RH158-24-100	24	94,37	66,5	40	600	45	0,34
RH158-12-200	12	198,5	69	40	1000	23	0,58
RH158-24-200	24	198,5	69	40	1000	23	0,29
RH158-12-250	12	243,8	69	40	1000	21	0,50
RH158-24-250	24	243,8	69	40	1000	21	0,25
RH158-12-510	12	512,85	72	40	1000	10,5	0,30
RH158-24-510	24	512,85	72	40	1000	10,5	0,15
RH158-12-630	12	629,82	72	40	1000	9	0,27
RH158-24-630	24	629,82	72	40	1000	9	0,135

